

**ARCHITECTURAL AND ENGINEERING SPECIFICATIONS
STEREO DOPPLER MICROWAVE INDOOR MONOSTATIC INTRUDER DETECTOR
PROTECH PIRAMD MW SERIES**

PART I GENERAL

1.01 PURPOSE

- A. The intent of these specifications is to describe the equipment and functional requirements of an outdoor intrusion detection sensor.

1.02 QUALIFICATIONS

- A. Brand names and catalog numbers included in the equipment or material specifications are used to establish standards of quality and performance characteristics, not for the purpose of limiting competitive bidding.

1.03 DESCRIPTION

- A. Indoor Monostatic (transmitter and receiver in one housing) volumetric microwave motion detector using the "Doppler" principle of transmitting a field of microwave energy into surveillance area so that an intruder's motion disturbs the field causing reflected signal to change
 - 1. Microwave Sensor: The microwave sensor shall use the "Doppler" principle of transmitting a field of microwave energy into surveillance area so that an intruder's motion disturbs the field, causing the reflected signal to change. The microwave sensor portion shall contain two receiving channels and use the "Stereo Doppler" technique, whereby the two received signals shall be compared to determine whether motion is moving toward or away from the sensor. An intruder moving a short distance (dependent on the sensitivity setting) in one direction shall cause an alarm; however, incidental vibration or fluctuating movement shall be rejected by the sensor's circuitry. The 10-position digital *Sensitivity Control Switch* shall adjust the microwave sensor detection sensitivity in 2" (5 cm) increments
- B. Fluorescent filter module (optional). FF-3 fluorescent filter shall be factory or field installed. Fluorescent filter shall notch out 60 Hz, 120 Hz, and 240 Hz for domestic operating frequencies (10.525 GHz USA). This option shall be installed on sensors that will be armed and operated in areas where fluorescent lighting will be left on during the protected hours and lighting fixtures are located in the sensors' field of view. (within 20 ft.).
- C. Sensor's relay shall change state in response to intrusion, tamper, and component failure alarms.

**STEREO DOPPLER MICROWAVE INDOOR MONOSTATIC INTRUDER DETECTOR
PROTECH PIRAMD MW SERIES**

1.04 SYSTEM CRITERIA

- A. Detection range shall be adjustable.
- B. Detection sensitivity shall be adjustable, enabling the selection of distance an intruder is required to move in one direction before causing an alarm.
- C. Circuit supervision shall cause a lock-in alarm condition with failure of a major component.
- D. Multiple sensors shall be usable in the same area without mutual interference.
- E. Sensor shall be equipped with Walk-Test and Environmental Caution Indicator lights with internal disable switch.
- F. Sensor shall be equipped with receptacle for plugging-in a sounder during set-up and walk-test.
- G. Sensor shall be equipped with Form C Relay with terminal connections.
- H. Sensor shall be equipped with housing tamper with terminal connections.
- I. Housing shall be metal, heavy-duty, and vandal resistant.
- J. Mounting shall be swivel type with 180 degree horizontal and 90 degree vertical adjustment.

PART II. SPECIFICATIONS

2.01 DESCRIPTION

A.	Operation	Alarm Output changes state when an intruder moves within protection pattern.
	Standard Protection Pattern	SDI-76MW 50ft. x 50ft. SDI-77MW 100ft. x 60ft.
	Power	8.5-20 VDC, 12 VDC Nominal
	Current	150 mA @ 12 VDC (LED's Off)
	Temperature	-30 to 130 degrees F(-34 to 54 degrees C)
	Humidity	0 to 100% Relative Humidity
	Conduit Knockout	for 1/2" conduit fitting (equipped with 90degree liquid tight elbow)
	Microwave Frequency Range	10,525 MHz USA International frequencies upon request
	Relay	Form C, Solid State Relay
	Relay Contact Rating	.1A, 50 V
	Tamper	Contacts closed in normal condition.