

## **PH-4EXWLMT INSTRUCTIONS**

### **Wall Mount Kit**

- 1 Each - EX-Wall Mount Kit  
Contains: Panavise Swivel, Model #400 MDT  
Stainless Steel Mounting Plate with Shaft
  
- 1 Each -Hardware Kit,  
Contains: 4 bolts (1/2" head)  
4 washers  
1 1/4" Allen Key

### **Required Tools**

- (1) Allen Key (included with kit)
- (2) 1/2" Socket

### **Assembly Instructions**

1. Hold the Panavise Swivel to the wall and mark the mounting hole patterns for the swivel.
  
2. Install the Panavise Swivel firmly to the wall.  
Note: The Panavise Swivel requires 4 each 5/16" bolts (not included with the EX Wall Mount).
  
3. Install the Stainless Steel Mounting Plate by inserting the shaft into the Panavise Swivel and tightening the plate onto the swivel using the provided Allen Key.



Figure 1  
EX Wall Mount Kit

3. Install 2 bolts with washers on the bottom side of the Base Plate as depicted in Figure 2.

Figure 2





Figure 3

4. Slide the SDI-77XL2-EX over the two Bolts on the bottom side of the base plate aligning the two feet on the bottom of EX housing with the two bolts on the bottom of the plate as depicted in Figure 3.
5. Install the two remaining bolts with washers through the two feet on the top of the EX housing into the top side of the base plate.
6. Tighten all four bolts with washers to firmly attach the EX Housing to the base plate.
7. Use the Allen Key to loosen the Panavise in order to aim Model SDI-77XL2-EX(EU) to the desired direction.



**CAUTION!**

**The PANAISE Model 400 Swivel Mount Bracket and the Stainless Steel Bracket may not be suitable for corrosive outdoor environments. Please use the **PH-4EXLMNT-C** for highly corrosive environments.**